

MANUFACTURER:

SaverSystems

Richmond, IN 47374

800-860-6327

Fax: 765-935-4999

www.1deck.com

DESCRIPTION

#1 Deck Advanced Solid Color Wood Stain is an extremely durable synthetic-resin, opaque wood finish that helps protect against the damaging effects of water, fungi, and UV radiation on exterior wood surfaces. This V.O.C. compliant water-based product provides a beautiful matte finish, fortified with transparent "oxide" based Nano Particles. There are over 30 TRILLION nano particles per square inch that provide extreme protection for your wood by blocking out the sun's harmful UV rays, moisture and fungal growth.

USES

#1 Deck Advanced Solid Color Wood Stain can be used on interior or exterior horizontal and vertical wood surfaces including: wood siding, log homes, decks, fences, outdoor wood furniture, pressure treated and all other natural wood surfaces.

ADVANTAGES

- Toughness and durability of "Nano Particle Technology"
- Completely hides wood grain
- Protects wood from graying, fading, & mildew
- Penetrating finish resists peeling
- Can be used on both horizontal and vertical wood surfaces
- Soap and water clean-up

SURFACE PREPARATION: Allow new wood to weather for three to six months to adequately dry out prior to application.

Clean: All wood surfaces must be clean, porous, and dry before applying #1 Deck Advanced Solid Color Wood Stain. Use #1 Deck Wood Cleaner to remove mill glaze, mildew, graying and other foreign matter that might block surface pores and interfere with product penetration. Rinse thoroughly with a garden hose or power washer (maximum 1200 p.s.i.). #1 Deck Wood Cleaner will darken redwood and some types of cedar; however, this darkening will disappear once the wood is treated with #1 Deck Wood Brightener.

Brighten: While surface is still wet from cleaning or stripping, use #1 Deck Wood Brightener to neutralize the wood, restore the wood to its natural color, and open the pores of the wood, allowing the stain to be more easily absorbed.

APPLICATION

Weather Conditions: Surface and air temperatures should be between 45°F and 95°F. Avoid application in direct sunlight. Do not apply to wet or water saturated surfaces, or when rain is expected within 12 hours. Stain may be applied to wood surfaces the same day as cleaning and brightening as long as surface is visibly dry before staining.

Mix well: Shake or stir contents before and periodically during use. To ensure absolute color uniformity from container to container, mix at least one third of the product from a used container with the contents of a new one. Do not thin product.

Protect adjacent areas: Use plastic, cardboard, and/or drop cloths to protect all adjacent non-targeted surfaces such as siding, windows, masonry, plant life, etc. from overspray and runoff. Immediately remove overspray from non-targeted areas with soap and water. Overspray that is allowed to dry will be difficult to remove; dried product cannot be removed from concrete and masonry.

Use the right equipment: Hand brushes should be high quality nylon or polyester. A paint roller may also be used. If using an airless sprayer, use tips between .013 and .015, and use the lowest pressure that achieves a uniform spray pattern to minimize fogging and overspray. To ensure a uniform finish, it is always best to back brush when spraying.

Decks: Start by applying #1 Deck Advanced Solid Color Wood Stain to the railings, benches, and undersides of upper level decks. Proper application requires 2 coats of product be applied, waiting for the first coat to dry before applying the second. Brush out all overspray, drips, etc. prior to them drying. Once all vertical surfaces have been treated with two coats of stain proceed to treating horizontal surfaces.

Horizontal surfaces: On all horizontal surfaces apply two coats of stain, waiting until the first coat has dried before proceeding to the second coat. Brush product into surface working out all drips, puddles, or areas of overspray before product dries. Complete entire sections or to a natural break before allowing to dry. Never break in the middle of a board. Thoroughly coat the ends of boards or logs to prevent water penetration. All surface checks on logs should be thoroughly coated.

Vertical Surfaces: Start from the bottom and work up. Treat the entire length of a board before moving up. If necessary, brush or feather in to avoid lap marks. Brush in product before it dries and work out drips, runs, or overspray.

Drying time: To touch, one to two hours depending on temperature and humidity. Allow 24 hours for deck to completely cure before using. High humidity and lower temperatures can greatly increase dry time.

Clean up: Clean tools and equipment immediately after each use with soap and water.

Coverage: With two coats, one gallon of #1 Deck Advanced Solid Color Wood Stain will cover approximately 100 - 150 sq. ft., depending on wood texture and porosity.

PRECAUTIONS

May cause an allergic skin reaction. **Keep out of reach of children.** Avoid breathing fumes, dust, mist, spray, vapor. Wear

eye protection, protective clothing, and protective gloves. Dispose of contents/container to comply with applicable local, national and international regulation.

FIRST AID

If inhaled: In all cases of doubt, or when symptoms persist, seek medical advice. Move the affected person away from the contaminated area and into the fresh air.

If swallowed: Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting unless directed to do so by a physician. If the person is fully conscious, make him/her drink water. Never give an unconscious person anything to drink. Immediately call a POISON CENTER or doctor/physician.

For skin contact: Remove/Take off immediately all contaminated clothing. Wash off immediately with soap and plenty of water. Obtain medical attention if irritation persists.

For eye contact: Immediately flush eyes thoroughly with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical attention immediately.

For additional information for this product, consult the Safety Data Sheet available at www.1deck.com.

SATISFACTION GUARANTEE

If you are not satisfied with the performance of this product, and providing you have followed label instructions, return the unused portion with a proof of purchase for refund or replacement of product. This guarantee does not include the cost of labor for removal or application of the product.

PACKAGING

Available in one-gallon recyclable plastic containers.

COLORS

#1 Deck Advanced Solid Color Wood Stain is available in 5 premixed colors: Simply White, Classic Taupe, Light Walnut, Dark Walnut, and Driftwood Gray.

TRANSPORT AND HANDLING

#1 Deck Advanced Solid Color Wood Stain is not considered hazardous under Department of Transportation regulations. Do not stack pallets. **Keep from freezing.**

CALIFORNIA PROP65 WARNING



This product can expose you to Benzophenone, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

PHYSICAL PROPERTIES

SOLVENT Water
VOC CONTENT <60 g/L
SHELF LIFE 36 months
FREEZE THAW STABILITY No